

Declaration of Performance

Document number 442014/0350117-116-101-100

1. Unique identification code of the product-type:

Purilan Euro 490x600

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

0350117 size 440x550 mm 0350116 size 440x550 mm 0350101 size 440x550 mm 0350100 size 440x550 mm

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roof window is designed for use in non-residential areas

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Ubbink by

Verhuellweg 9 P.O. Box 26 6980 AA Doesburg The Netherlands

Phone: +31 (0)313 480 200

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised

Name and number of the technical assessment body:

0620

Performed:

EN 14 351 - 1:2006 + A1:2010

Under system:

System 3

And issued:

Test Reports

8. In case of the declaration of performance concerning a construction product for which a European Technical Assesment has been issued:

Name and number of the technical assessment body:

Not applicable

Issued:

Not applicable

On the basis of:

Not applicable



9. Declared performance

	Essential Characteristics	Performance	Harmonized technical Specification
9.1	External fire performance	Npd*	PN-EN 14351-1
9.2	Reaction to fire	Npd*	PN-EN 14351-1
9.3	Watertightness	5-A	PN-EN 14351-1
9.4	Resistance to windload	Npd*	PN-EN 14351-1
9.5	Resistance to snow and permanent load	4-14-4 glass	PN-EN 14351-1
9.6	Impact resistance	Npd*	PN-EN 14351-1
9.7	Load-bearing capacity of safety devices	Npd*	PN-EN 14351-1
9.8	Acoustic performance	Npd*	PN-EN 14351-1
9.9	Thermal transmittance	3,2 W/m2*K	PN-EN 14351-1
9.10	Radiation properties	0,62	PN-EN 14351-1
9.11	Air permeability	Class 2	PN-EN 14351-1

^{*}npd - no performance determined

10. The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in Point 4.

On behalf of the manufacturer

Doesburg, November 05 - 2014

Henk-Jan Wegman

Managing Director, Ubbink BV