



Declaration of Performance

Document number 452014 0331804_10_27_34_41_58_65 0331700-94

1. Unique identification code of the product-type:

Purilan

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

0331804 size 490x590 mm
0331810 size 490x590 mm
0331827 size 490x590 mm
0331834 size 490x590 mm
0331841 size 490x590 mm
0331858 size 490x590 mm
0331865 size 490x590 mm
0331700 size 425x800 mm
0331794 size 425x800 mm

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roof window is intended to be used in non-residential areas

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Ubbink bv
Verhuellweg 9
P.O. Box 26
6980 AA Doesburg
The Netherlands
Phone: +31 (0)313 480 200

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name and number of the technical assessment body: **0620**
Performed: **EN 14 351 – 1:2006 + A1:2010**
Under system: **System 3**
And issued: **Test Reports**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Name and number of the technical assessment body: **Not applicable**

Issued: **Not applicable**

On the basis of: **Not applicable**

9. Declared performance

	Essential Characteristics	Performance	Harmonized technical Specification
9.1	External fire performance	Npd*	PN-EN 14351-1
9.2	Reaction to fire	Npd*	PN-EN 14351-1
9.3	Watertightness	2a	PN-EN 14351-1
9.4	Resistance to windload	Npd*	PN-EN 14351-1
9.5	Resistance to snow and permanent load	3-8-3 glass	PN-EN 14351-1
9.6	Impact resistance	Npd*	PN-EN 14351-1
9.7	Load-bearing capacity of safety devices	Npd*	PN-EN 14351-1
9.8	Acoustic performance	Npd*	PN-EN 14351-1
9.9	Thermal transmittance	5,4 W/m ² K	PN-EN 14351-1
9.10	Radiation properties	0,79	PN-EN 14351-1
9.11	Air permeability	Class 3	PN-EN 14351-1

*npd – no performance determined

10. The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in Point 4.

On behalf of the manufacturer



Doesburg, November 05 – 2014

Henk-Jan Wegman
Managing Director, Ubbink BV